


Simulated annealing optimization of walls, portal and box reinforced concrete road structures

by

Vidosa, Yepes, Alcalá, Carrera and Perea




Technical University of Valencia
Department of Construction Engineering
Spain




1. Structures object of the study.


- A) Cantilever RC earth retaining walls
(Internal Report CST/GPRC-01, Alcalá)



- B) Portal RC road frames
(Internal Report CST/GPRC-02, Carrera)





- C) Box RC road frames
(Internal Report CST/GPRC-03, Perea)




2. Variables and parameters.

- 2.1. Walls: 26 continuous and discrete variables:
- 4 geometrical
 - 4 concrete and steel grades
 - 18 variables of steel reinforcement setup




2. Variables and parameters.

2.2. Variables for the RC portal road frames: 28 variables; 5 geometrical, 3 concrete grades and 20 types of steel reinforcement.



2. Variables and parameters.

2.3. Variables for the box frame road structures: 44 variables: 2 geometrical, 2 concrete grades and 40 types of steel reinforcement.



3. Feasibility of solutions.

- Loads according to national IAP prescriptions for road bridges.
- ULS:
 - sliding and overturning (only walls)
 - flexure
 - shear
- SLS:
 - flexure (cracking control)
 - deflections:
 - 1/150 in walls
 - 1/250 for quasipermanent loading in frames
- Fatigue of concrete (box frames only)

4. Optimization procedure method.



SIMULATED ANNEALING:

$$e^{-\Delta C/T}$$

$$T_{i+1} = k T_i$$

Initial temperature (Medina)

Markov chains

Cooling coefficient

Methodology

step 1 – Generation of random solutions (random walk)

step 2 – Study of best moves by descent local search


step 3 – Calibration of simulated annealing / threshold accepting methods

(9 runs per analysis: minimum, mean and standard deviation)

5. Results

5.1. Wall of 7.0 m height.

Variable	Permissible stress = 0.3 N/mm ²		
	Reference	Deflections unrestricted	Deflections limited
b	0.25-0.70 m	0.265 m	0.607 m
p	0.75 m	0.833 m	0.770 m
t	1.70 m	1.248 m	0.900 m
c	0.70 m	0.568 m	0.605 m
f _{ck,ste}	25	35	30
f _{ck,foo}	25	25	25
f _{yk,ste}	500	500	500
f _{yk,foo}	500	500	500
A ₁	7.70 cm ²	6.946 cm²	11.442 cm²
A ₂	7.70 cm ²	29.602 cm²	1.431 cm²
A ₃	0	26.730 cm²	10.332 cm²
A ₄	4.35 cm ²	1.000 cm ²	1.149 cm ²
A ₅	3.74 cm ²	3.400 cm ²	6.552 cm ²
A ₆	7.73 cm ²	5.661 cm ²	13.120 cm ²
A ₇	0	0	0
A ₈	13.40 cm ²	16.837 cm ²	16.958 cm ²
A ₉	10.05 cm ²	1.000 cm ²	17.013 cm ²
A ₁₀	0	19.549 cm ²	1.000 cm ²
A ₁₁	0	1.447 cm ²	1.000 cm ²
A ₁₂	3.74-1.67 cm ² (low-up)	3.955 cm ²	8.776 cm ²
A ₁₃	0	0	0
L ₁	2.18 m	2.954 m	0.849 m
L ₂	0	0.852 m	0.834 m
L ₃	0	0	0
L ₄	0	1.248 m	0.745 m
L ₅	0	0.568 m	0.689 m



Simulated annealing data:

- Markov chains of 1000 iterations
- Cooling coefficient of 0.80
- Best move 16 in 26 variables
- Running time 21 minutes in Visual Basic 6.3 with an Excel I/O interface

Conclusion:

Importance of limitation of the deflection of the stem


5. Results

5.2. Portal frame case study B.

Geometric variables	
h	0.375 m
b	0.400 m
c	0.400 m
p	0.950 m
t	0.750 m
Concrete grades	
upper slab	HA-25
wall	HA-25
foundation	HA-25
Reinforcement	
A ₁	15ø12/m
A ₂	10ø20/m
A ₆	12.06 cm ² /m
A ₇	15ø12/m
A ₈	8ø16/m
A ₉	12ø8/m
A ₁₅	10ø16/m
A ₁₆	12ø10/m
A ₂₀	9.05 cm ² /m

Simulated annealing data:

- Markov chains of 375 iterations
- Cooling coefficient of 0.70
- Best move 4 in 28 variables
- Running time 10.75 hours in an AMD 1.49 GHz in Visual Basic 6.3




Conclusion: Importance of including fatigue of concrete.

5. Results

5.3. Box frame case study C.

Simulated annealing data:

- Markov chains of 500 iterations
- Cooling coefficient of 0.90
- Best move 9 in 44 variables
- Running time 47 minutes in an Pentium IV 2.40 GHz in Fortran




Conclusion: Importance of including fatigue of concrete and deflections.

7. Conclusions.

- Simulated annealing feasibility as an optimization procedure for RC road structures.
- Importance of limiting the deflections in wall analysis.
- Importance of deflections and fatigue of concrete in analysis of frame road structures.

8. Current and future work.

- Building frames
- Vaults
- Abutments of bridges
- Bridge hollow piers
- Prestressed concrete slab-decks for flyovers
- Composite decks for flyovers



Simulated annealing optimization of walls, portal and box reinforced concrete road structures

by

Vidosa, Yepes, Alcalá, Carrera and Perea



Technical University of Valencia
Department of Construction Engineering
Spain

